

NEW

C3606DPA

Cordless Plunge
Cut Saw

36V - Ø165 mm

BRUSHLESS

Fast stopping brake

Full guide rail compatability

66 mm cutting depth, 61 mm on guide rail



Specifications

Voltage	36V
No-load speed	2,500 - 5,200 /min.
Saw blade diameter	165 mm
Mount hole diameter	20 mm
Maximum cutting depth	90° 66 mm
	45° 43 mm
Max. cutting depth with guide rail	61 mm
Cutting depth adjustability	0 - 66 mm
Bevel capacity	-1°/46°
Brushless motor	✓
Guide rail compatability	✓
Variable speed	✓
Brake	✓
LED	✓
Soft start	✓
Dimensions (L x W x H)	391 x 206 x 269 mm
Weight with BSL36A18X ¹	5.4 kg

Characteristics

Extremely powerful and the greatest maximum cutting depth of 66 mm in its class

Compatible with HIKOKI guide rails and common guide rails of other brands (Makita, Bosch, Festool, Hilti, and others) for maximum flexibility

Variable speed setting for the right speed for each material

Fast stopping brake for high user safety

Undercut function (-1°/46°) enables precise fitting cuts of the workpiece

Double depth adjustment indication for a precise depth adjustment with and without guide rail

Versions²

C3606DPAWVZ:	2x battery BSL36B18X, fastcharger UC18YSL3, dust bag, saw blade, stackable case HSC IV
C3606DPAW2Z:	Dust bag, saw blade, stackable case HSC IV
KSC3606DPAWV1Z:	2x battery BSL36B18X, fastcharger UC18YSL3, dust bag, saw blade, stackable case HSC IV, guide rail 160 cm
KSC3606DPAW21Z:	Dust bag, saw blade, stackable case HSC IV, guide rail 160 cm

¹ With torque boost technology.

² Weight according to EPTA-2004 procedure.

³ Standard accessories vary by country or area.

Read everything
about our services at
hikoki-powertools.eu

