

NEW

C3607DB

Cordless Circular Saw

36V - Ø190 mm - 64.5 mm

**TORQUE
Boost
BRUSHLESS**

Cutting depth of 64.5 mm

Torque Boost motor technology

Guide rail adapter included

Big rafter hook



Specifications

Voltage	36V
No-load speed	4,500 - 6,000 /min.
Saw blade diameter	190 mm
Mount hole diameter	30 mm
Maximum cutting depth 90°	64.5 mm
Maximum cutting depth 45°	49 mm
Bevel capacity	0°/45°
Brushless motor ¹	✓
Guide rail compatibility	✓
Rafter hook	✓
Brake	✓
LED	✓
Soft start	✓
Constant speed control	✓
Kickback protection	✓
Dimensions (L x W x H)	313 x 221 x 280 mm
Weight with BSL36A18X ²	4.3 kg

Characteristics

Torque Boost motor technology:

- Auto switch mode for fastest cuts and automatic detection of the right motor setting
- Torque mode for powerful and battery saving cuts

Included guide rail adapter for compatability with guide rails from HiKOKI, Makita, Milwaukee, and Hilti

Big rafter hook for convenient storage on the jobsite in working brakes

Fast stopping brake and kickback protection for high user safety

Robust design and high power for fast cuts in harsh environments and various materials such as wet wood

Versions³

2x BSL36A18X battery, fastcharger UC18YSL3, guide rail adapter, rafter hook, dust adapter, saw blade wood, hex key, stackable case HSC IV, 160 cm guide rail, carton

C3607DBWRZ: 2x BSL36A18X battery, fastcharger UC18YSL3, guide rail adapter, rafter hook, dust adapter, saw blade wood, hex key, stackable case HSC IV

KSC3607DBW21Z: Guide rail adapter, rafter hook, dust adapter, saw blade wood, hex key, stackable case HSC IV, 160 cm guide rail, carton

C3607DBW2Z: Guide rail adapter, rafter hook, dust adapter, saw blade wood, hex key, stackable case HSC IV

¹ With Brushless Torque Boost motor technology.

² Weight according to EPTA-2004 procedure.

³ Standard accessories vary by country or area.

Read everything
about our services at
hikoki-powertools.eu

