

NEW

CV350V2

Multitool

230V - 350 W

Updated locking mechanism

Wide range of
accessories available

350 W motor with
overload protection



Specifications

Voltage	230V
Input power	350 W
No-load oscillation frequency	6,000 - 20,000 /min.
Oscillating angle	3.2°
Accessory system	OIS (Starlock compatible)
Variable speed	✓
Toolless accessory change	✓
Soft start	✓
Constant speed control	✓
Auto mode	✓
Cord length	2.5 m
Dimensions (L x H)	280 x 100 mm
Weight ¹	1.5 kg

Characteristics

Updated locking mechanism for a fast tool-free change of accessories

Wide range of optional HiKOKI accessories available

350 W motor with overload protection for a fast and durable working process

Variable speed regulation for the right speed for each application

Non-snapping, very smooth closing accessory locking lever for safe change of accessories

Versions²

CV350V2-W1Z:	Cutting blade wood/metal, sanding pad, 10x sanding paper (P80, P120), stackable case HSC II
CV350V2-W2Z:	Cutting blade wood/metal, stackable case HSC II
CV350V2-W4Z:	Cutting blade wood/metal, cardboard box

¹Weight according to EPTA-2004 procedure.

²Standard accessories vary by country or area.

Read everything
about our services at
hikoki-powertools.eu



More information about the product at
hikoki-powertools.eu