

DS36DC

Cordless Driver Drill

36V

BRUSHLESS
RFC

NEW

Industry's top class power - 155 Nm

Robust aluminium gear housing

Reactive Force Control with Gyro sensor



Specifications

Voltage		36V
Max. capacity drilling	Wood	118 mm
	Metal	20 mm
Max. capacity screwing	Wood screw	16 mm x 100 mm
	Machine screw	6 mm
Capacity drill chuck		13 mm
Max. torque	Hard joint	155 Nm
	Soft joint	100 Nm
No-load speed	Low mode	0 - 550 /min.
	High mode	0 - 2,200 /min.
Slip torque	Stages	22
	Torque	1.5 to 8.0 Nm
Motor type		Brushless
Anti-kickback function (RFC with Gyro sensor)		Yes
Dimensions L x H x W		190 x 267 x 70 mm
Weight ¹	With BSL36A18	2.8 kg
	Without battery	2.1 kg

Characteristics

Industry's top class power and drilling speed for toughest applications
Improved airflow design and heat sink keep electronics cool
Robust aluminium gear housing provides additional rigidity
RFC technology and a Gyro sensor detect overburdening of the tool bit and stop the motor to reduce twisting of the main unit
Compact body to work in tight and hard to reach spaces
Constant speed control provides additional power so that the motor can maintain its speed under load
Metal chuck with carbide inserts for highest gripping force
Rotatable side handle provides ease of use and simplicity of operation
Ergonomic soft grip handle for optimal control and longer comfortable working

Versions²

DS36DCWRZ: 2x battery BSL36A18, charger UC18YSL3, stackable case HSC II
DS36DCW2Z: Stackable case HSC II
DS36DCW4Z: Cardboard box

¹ Weight according to EPTA-2004 procedure.

² Standard accessories vary by country or area.

