



18 V brushless concrete nailer for drywall applications with nails up to 40 mm

- HiKOKI air-spring drive system for 25 % lower operating costs compared to gas-powered nailers - quiet and emission-free
- Constantly high impact energy of 110 joules for maximum performance and reliable fastening even in dense concrete
- Slim design, especially for working in 50x50 mm drywall profiles
- Two-stage depth adjustment prevents driving in too deep to protect concrete surfaces and metal profiles
- Magazine and nose can be removed without tools for quick release of jammed nails for fast continuation of work
- Long-lasting gearbox thanks to easy detection and readjustment of driver blade in case of misalignment
- Electrical dry-fire lockout mechanism activates when magazine is empty to protect workpiece
- Integrated, foldable stand - cannot be lost
- Integrated LED work light for safe, precise work

Product ID EAN

NC1840DAW3Z
4966376417926

Battery voltage	18 V
Nailing speed	1.5 s
Nail collation type	Plastic Collated
Nail collated angle	0°(Full Round Head)
Nail length	15 - 40 mm
Wire collated nails length	x mm
Magazin capacity (nails)	25
Weight (without battery pack)	4.1 kg
Weight (with battery pack)	4.1
Weight	4.1 kg
Tool length	330 mm
Tool width	120 mm
Tool height	400 mm
Driving system	DC (Air Spring)
Depth adjuster	Yes
Contact actuation mode	No
Kickback reduction	No
Dry-fire lockout	Yes
Blow function	No
LED light	Yes
Brushless	Yes

Standard Accessory Supplied

Safety glasses, Blow Case